



DC/DC 新能源高压电源模块

Jwdx--10W 新能源高压电源模块单路系列

Jwdx--5W New energy high input power supply module single output series

典型性能 Typical Performance

- ◆ 外形尺寸: 72*50*28 (mm)
Dimension: 72*50*28 (mm)
- ◆ 宽输入电压范围 (6:1 和 10: 1 输入电压范围)
Wide range input voltage (6: 1 & 10: 1 range input voltage)
- ◆ 高效率、高功率密度、低纹波
High efficiency、High power density、Low ripple & noise
- ◆ 黑金属外壳，八面屏蔽，通孔安装
Black metal shell, Eight face shield, Hole is installed
- ◆ 安规: EN60950
Ann rules: EN60950



输入特性 Input Features

输入电压范围 Input voltage range	标称 700V Nominal voltage 700V 标称 1100V Nominal voltage 24V	200~1200VDC 200~2000VDC
输入冲击电流 Inrush current	200V 600V 1200V 2000V	≤7A ≤20A ≤35A ≤50
输入欠压保护 Input under-voltage protection	欠压保护点 Under-voltage protection point	175~185V

输出特性 Output Features

输出电压精度 Voltage tolerance	标称电压 Nominal voltage	≤ ±1% (5V ≤ ±2%)
电压调整率 Line regulation (full load)	输入电压从低端到高端变化 Change of input voltage from lowend to highend	≤ ±0.5%
负载调整率 Load regul	20%~100% 负载变化 20%~100% Load change	V _O ≤ ±0.5%
温度系数 Temperature coefficient		±0.02%/°C
过流保护 Output overcurrent Protection		115~150% 额定电流, 自恢复 115~150% rated output circuit, auto recovery
短路保护 Short Circuit Protection		长期, 自恢复 Long-term, auto recovery
输出过压保护 Output over voltage protection	输出 5V Output 5V 输出 12V Output 12V 输出 24V Output 24V	≤ 7.5V ≤ 15V ≤ 27V

一般特性 General Features

隔离耐压 Withstand voltage	输入对输出 (1分钟, 漏电流 ≤ 5mA) I/P-O/P (1Mintute, leakage current) ≤ 5mA	4000VDC
绝缘电阻 Isolation resistance	1000V	≥ 100MΩ
MTBF	环境 25°C Environment 25°C	2.0*10 ⁵ Hrs
开关频率 switching frequency		65KHz
工作温度 Operating temperature	55°C 以上降额使用 Above 55°C derating make	-40°C~70°C
储存温度 Storage temperature		-40°C~85°C
工作相对湿度 Operating humidity	无凝露及结冰现象 (non condensing)	10%~90%RH
储存相对湿度 Storage humidity	无凝露及结冰现象 (non condensing)	5%~95%RH
冷却方式 Cooling method		自然冷却 Convection

命名方式 Naming Rules

Jwdx 10 -700 S 5

输出电压
Output voltage
单路输出
Single Output
标称输入电压
Nominal Input voltage
输出功率
Output power
新能源产品
New energy product
DC/DC 电源模块
DC/DC power module

产品选型 Product selection

产品型号 Model No.	输入电压范围 Input voltage V _{in}	输出电压 Output voltage V _o	输出电流 Output current I _o	纹波噪声 R & N V _{(P-P)mV}	效率 Efficiency
Jwdx10-700S5	200~1200V	5V	2.00A	80	75%
Jwdx10-700S12		12V	0.84A	100	78%
Jwdx10-700S24		24V	0.42A	120	82%
Jwdx10-1100S5	200~2000V	5V	2.00A	80	75%
Jwdx10-1100S12		12V	0.84A	100	78%
Jwdx10-1100S24		24V	0.42A	120	82%


注：因篇幅有限，以上只是部分产品列表，若需列表以外产品，请与本公司销售部联系。

输出纹波噪声（峰-峰值）的测量，请参照模块测试说明中介绍的方法进行。

Note: Due to space limitations ,the above list is only for some products, If other than a list of products, please contact the Company's sales department.

Output ripple noise measurement (peak - peak), please refer to the module test notes method is introduced.

封装尺寸图 MechanicalData




管脚定义 Pin Assignments

P1	P2	P3	P4	P5	P6	P7	P8
NP	V _{in+}	V _{in-}	V _{o+}	NP	GND	NP	GND

典型曲线 Typical curve


降额曲线

Derating curve



效率曲线

Efficiency curve



纹波噪声测试: (靠测法 20MHz)

测试方法: 纹波&噪声用示波器来测试。测试模块噪声时为了避免引入额外噪声, 须用示波器探头直接接触模块输出引脚

