



AC/DC 整机工控电源

JWAK 整机工控电源系列--50W 双路输出

JWAK Switching Power Supply Series --50W Dual Output

典型性能 Typical Performance

- ◆ 外形尺寸: 130*98*40 (mm)
Dimension: 130*98*40 (mm)
- ◆ 宽输入电压范围
Wide range input voltage
- ◆ 高效率、高功率密度、低纹波
High efficiency、High power density、Low ripple & noise
- ◆ 105°C长寿命电解电容
105°C long life electrolytic capacitors
- ◆ 高可靠性、三年保修
High reliability、three-year warranty
- ◆ 安规: EN60950
Ann rules: EN60950



输入特性 Input Features

输入电压范围 Input voltage range	W:85~265VAC 120~370VDC N:165~265VAC 230~370VDC	110VAC 220VAC
输入电压频率 Input voltage frequency		47~63Hz
输入冲击电流 Inrush current	230VAC 冷启动 230VAC Cold start,	≤30A

输出特性 Output Features


输出电压精度 Voltage tolerance	标称电压 Nominal voltage	$V_{o1} \leq \pm 1\%$ (3.3V、5V $\leq \pm 2\%$), $V_{o2} \leq \pm 5\%$
电压调整率 Line regulation (full load)	输入电压从低端到高端变化 Change of input from lowend to highend	$V_{o1} \leq \pm 0.5\%$, $V_{o2} \leq \pm 1.5\%$
负载调整率 Load regul	20%~100%负载变化 20%~100% Load change	$V_{o1} \leq \pm 0.5\%$, $V_{o2} \leq \pm 3\%$
温度系数 Temperature coefficient		±0.02%/°C
过功率保护 Output overload Protection		115~150%额定电流,自恢复 115~150%rated output power, auto recovery
短路保护 Short Circuit Protection		长期, 自恢复 Long-term, auto recovery
效率 Efficiency	输入标称电压、满载 Input rated voltage、full load	80% (典型值) 75%(typical)
启动时间 Rise time	220VAC 满载 220VAC Full load	50mS (典型值) 50ms (typical)
保持时间 Hold up time	220VAC 满载 220VAC Full load	20mS (典型值) 50ms (typical)

一般特性 General Features


隔离耐压 Withstand voltage	输入对输出、输入对地 I/P-O/P, I/P-F/G 输出对地 O/P -F/G 输出对输出 (隔离) O/P-O/P (1分钟, 漏电流 $\leq 5mA$) (1Minute leakage current) $\leq 5mA$)	1500VAC 500VAC 500VDC
绝缘电阻 Isolation resistance	500V	$\geq 50M\Omega$
MTBF	环境 25°C Environment 25°C	2.0×10^5 Hrs
工作温度 Operating temperature	55°C以上降额使用 Above 55°C derating make	-25°C~70°C(-40°C~70°C)
储存温度 Storage temperature		-40°C~85°C
工作相对湿度 Operating humidity	无凝露及结冰现象 (non condensing)	10%~-90%RH
储存相对湿度 Storage humidity	无凝露及结冰现象 (non condensing)	5%~-95%RH
冷却方式 Cooling method		自然冷却 Convection

命名方式 Naming Rules

JWAK- 50 D 5 W(N)



输入电压范围 (W:85~265V, N:165~265V)
Input voltage range (W:85~265V, N:165~265V)
输出电压
Output voltage
双路共地输出
Dual common-GND output
输出功率
Output power
AC/DC 工控电源
AC/DC Switching Power Supply



产品选型 Product Selection Table

产品型号 Model No.	输出电压 Output voltage Vo	输出电流 Output current Io	输出电压精度 Output voltage tolerance	纹波噪声 R&N V _{(P-P)mV}	效率 Efficiency
JWAK-50D5W(N)	+ 5V	0.5~5.0A	±2%	80mV	76%
	-5V	0.5~5.0A	±5%	100mV	
JWAK-50D12W(N)	+12V	0.2~2.1A	±1%	100mV	80%
	-12V	0.2~2.1A	±5%	100mV	
JWAK-50D15W(N)	+ 15V	0.2~1.7A	±1%	100mV	81%
	-15V	0.2~ 1.7A	±5%	100mV	
JWAK-50D24W(N)	+24V	0.1~1.0A	±1%	150mV	83%
	-24V	0.1~ 1.0A	±3%	150mV	
JWAK-50S5S9W(N)I	+5V	1.0~ 8.0A	±2%	80mV	78%
	+9V	0.1~1.0A	±5%	100mV	
JWAK-50S5S12SW(N)I	+5V	0.6~6.0A	±2%	100mV	79%
	+12V	0.2~1.5A	±3%	120mV	
JWAK-50S5S15W(N)I	+ 5V	0.7~7.0A	±2%	100mV	80%
	+15V	0.1~ 1.0A	±3%	120mV	
JWAK-50S5S24W(N)I	+5V	0.5~ 5.0A	±2%	100mV	81%
	+24V	0.1~1.0A	±3%	150mV	
JWAK-50S12S5SW(N)I	+12V	0.4~3.5A	±1%	120mV	79%
	+5V	0.1~1.0A	±5%	100mV	
JWAK-50S15S5W(N)I	+ 15V	0.3~3.0A	±1%	120mV	80%
	+5V	0.1~ 1.0A	±5%	100mV	
JWAK-50S24S5W(N)I	+ 24V	0.2~1.5A	±1%	150mV	82%
	+5V	0.1~ 1.0A	±5%	100mV	


注：1、续波保声测试方法：使用一根12芯绞线，在其端开联0.1μF和1μF电容，在20MHz带宽下测试。

e: 1、 Ripple & noise are measured at 20MHz of bandwidth by using a 12"twisted pair.

2. Due to space limitations ,the above list is only for some products, If other than a list of products, please contact the Company's sales de-

Due to space limitations, the above lists only a few items. For more products, or other than listed products, please contact the company's sales department.

安裝尺寸圖 Mechanical Data



注：电源安装尺寸如与选型手册不符，请以实物尺寸为准。

Note: Power mechanical data does not match with the hand book, Please refer to product size

典型曲线 Typical curve

降额曲线
Derating curve

静态特性曲线 Output Derating VS Input Voltage curve

