



## DC/DC 整机工控电源

### JWDK 整机工控电源系列--50W 单路输出

JWDK Swittching Power Supply Series--50W Single Output

#### 典型性能 Typical Performance

- ◆ 外形尺寸: 130\*98\*40 (mm)  
Dimension: 100\*584\*31 (mm)
- ◆ 宽输入电压范围 (2: 1 输入电压范围)  
Wide range input voltage (2: 1 range input voltage)
- ◆ 高效率、高功率密度、低纹波  
High efficiency、High power density、Low ripple & noise
- ◆ 低漏电流、过流恒流保护  
Low leakage current, Over current protection with constant current
- ◆ 金属外壳，八面屏蔽，  
Metal shell, Eight face shield
- ◆ 安规: EN60950  
Ann rules: EN60950



#### 输入特性 Input Features

输入电压范围 Input voltage range	标称 48V Nominal voltage 12V 标称 105V Nominal voltage 24V 标称 225V Nominal voltage 48V 标称 575V Nominal voltage 48V	24~70VDC 30~180VDC 70~380VDC 350~800VDC
-------------------------------	---	--

#### 输出特性 Output Features

输出电压精度 Voltage tolerance	标称电压 Nominal voltage	$\leq \pm 1\%$ (3.3V、5V $\leq \pm 2\%$ )
电压调整率 Line regulation (full load)	输入电压从低端到高端变化 Change of input voltage from lowend to highend	$\leq \pm 0.5\%$
可调范围 Adjustment range		$\pm 10\%$
负载调整率 Load regul	20%~100% 负载变化 20%~100% Load change	$V_O \leq \pm 0.5\%$
纹波噪声 Ripple&Noise	20M 带宽 20M Bandwidth	$\leq 1\%$
温度系数 Temperature coefficient		$\pm 0.02\%/\text{°C}$
过流保护	恒流保护	115~150% 额定电流, 自恢复


Output overcurrent Protection	constant current	115~150% rated output circuit, auto recovery
短路保护 Short Circuit Protection		长期, 自恢复 Long-term, auto recovery
过冲幅度 Overshoot	25% 额定负载变化 25% rated load change	$\leq 25\mu s$
	$\Delta V_{01} / V_{01}$	$\leq \pm 5.0\%$

## 一般特性 General Features

隔离耐压 Withstand voltage	输入对输出、输入对地 I/P-O/P、 I/P-F/G 输出对地 O/P -F/G (1分钟, 漏电流 $\leq 2mA$ ) (1Mintute leakage current) $\leq 2mA$ )	2500VAC 500VAC
绝缘电阻 Isolation resistance	500V	$\geq 50M\Omega$
MTBF	环境 25°C Environment 25°C	$2.0 \times 10^5$ Hrs
工作温度 Operating temperature	55°C 以上降额使用 Above 55°C derating make	-25°C ~ 70°C (-40°C ~ 70°C)
储存温度 Storage temperature		-40°C ~ 85°C
工作相对湿度 Operating humidity	无凝露及结冰现象 (non condensing)	10% ~ 90% RH
储存相对湿度 Storage humidity	无凝露及结冰现象 (non condensing)	5% ~ 95% RH
冷却方式 Cooling method		自然冷却 Convection

## 命名方式 Naming Rules

JWDK50-48 S 5




## 产品选型 Product selection

产品型号 Model No.	输入电压范围 Input voltage $V_{in}$	输出电压 Output voltage $V_o$	输出电流 Output current $I_o$	纹波噪声 R & N $V_{(P-P)mV}$	效率 Efficiency
JWDK50-48S5	24~70V	5V	10.0A	100	79%
JWDK50-48S12		12V	4.2A	120	81%
JWDK50-48S24		24V	2.1A	150	83%
JWDK50-105S5	30~180V	5V	10.0A	100	79%
JWDK50-105S12		12V	4.2A	120	81%
JWDK50-105S24		24V	2.1A	150	83%
JWDK50-225S5	70~380V	5V	10.0A	100	79%
JWDK50-225S12		12V	4.2A	120	82%
JWDK50-22524		24V	2.1A	150	84%
JWDK50-575S5	350~800V	5V	10.0A	100	79%
JWDK50-575S12		12V	4.2A	120	82%
JWDK50-57524		24V	2.1A	150	84%

注：因篇幅有限，以上只是部分产品列表，若需列表以外产品，请与本公司销售部联系。

Note: Due to space limitations ,the above list is only for some products, If other than a list of products, please contact the Company's sales department.

## 安装尺寸图 MechanicalData



注：电源安装尺寸如与选型手册不符，请以实物尺寸为准。

Note: Power mechanical data does not match with the hand book, Please refer to product size